

HPT-BZ-32P-0738-65R1517-E

Base Station Antenna

Features:

- 2*690-960/2*1427-2690/2*1695-2200/2*2490-2690
- 32Port(16-Port 4.3/10(F) 2-Port MQ4+MQ5)
- Each Band Individually Adjustable



Electrical Properties

Frequency range (MHz)		2*(690–960) (R1/R2)				2*1710-2170(B1/B2)		2*(2490–2690) (Y1/Y4)
		690–803	790–862	824–894	880–960	1695–1990	1920–2200	2490-2690
Gain (dBi)	At mid tilt	15.1	15.4	15.4	15.6	17.2	17.4	17.8
	Over all tilts	14.9±0.5	15.2±0.5	15.2±0.5	15.4±0.5	17.0±0.8	17.4±0.6	17.7±0.5
Side lobe suppression for first side lobe above main beam (dB)		> 15	> 15	> 15	> 15	>15	>15	>15
Horizontal 3 dB beam width (°)		69±6	66±6	63±6	60±6	63±6	62±5	58±7
Vertical 3 dB beam width (°)		10.9±1	9.8±0.8	9.4±0.7	8.9±0.6	7.9±0.6	7.1±0.6	5.8±0.5
Max. power per input (W)		300 (at 50°C ambient temperature)				150 (at 50°C ambient temperature)		

Electrical Properties

Frequency range (MHz)		2* (1427–2690) (Y2/Y3)				
		1427-1518	1695–1990	1920–2200	2200–2490	2490–2690
Gain (dBi)	At mid tilt	16.6	17	17.4	17.7	17.8
	Over all tilts	16.5±0.5	16.9±0.5	17.3±0.5	17.6±0.5	17.7±0.5
Side lobe suppression for first side lobe above main beam (dB)		> 15	> 15	> 15	> 15	> 15
Horizontal 3 dB beam width (°)		72±6	63±6	62±5	60±6	58±7
Vertical 3 dB beam width (°)		9.3±0.6	7.9±0.6	7.1±0.6	6.4±0.5	5.8±0.5
Max. power per input (W)		150 (at 50°C ambient temperature)				
Polarization		±45°				
Electrical downtilt (°)		2–12,				
VSWR		< 1.5				
Cross polar isolation (dB)		>25				
Interband isolation (dB)		≥ 28				
Front to back ratio, ±30° (dB)		>25				
Cross polar ratio, 0° (dB)		16				
Intermodulation IM3 (dBc)		≤ –153 (2 x 43 dBm carrier)				
Impedance (Ω)		50				
Grounding		DC grounding				

Electrical Properties

		P1、P2 2300-3800		
		2300-2690	3300-3800	
General parameters	Frequency range (MHz)			
	Polarization	±45°		
	Electrical down-tilt (°)	2-12		
	Impedance (Ω)	50		
	Lightning Protection	DC Ground		
Calibration And electrical parameters	Coupling factor between calibration port and each antenna port (dB)	-26±2		
	Max. amplitude tolerance from calibration port to input ports (dB)	≤1.0		
	Max. phase tolerance from calibration port to input ports (°)	≤10		
	Ports VSWR	<1.5		
	Avg. power capacity (W)	50		
	Intra-band isolation (dB)	≥20		
	Inter-band isolation (dB)	≥20		
Radiation parameters	Single column beam	Horizontal 3dB beam width (°)	90	65
		Gain (dBi)	14.7	15.7
		Vertical-3dB Beamwidth (°)	8.3	6.1
		Cross Polar Discrimination at Boresight (dB)	≥15	≥15
		First upper side lobe suppression (dB)	≥15	≥15
		Front to back ratio (dB)	≥25	≥23
	65° Broadcast Beam	Horizontal 3dB beam width (°)	65	65
		Gain (dBi)	16.0	16.8
		Vertical-3dB Beamwidth (°)	8.3	6.1
		Cross Polar Discrimination at Boresight (dB)	≥15	≥15
		Front to back ratio (dB)	≥25	≥25
		First upper side lobe suppression (dB)	≥15	≥15
	Service beam	0° direct beam gain (dBi)	20.0	21.0
		0° direction beam horizontal 3dB beam width (°)	27	18
		0° direction beam cross polar ratio at Boresight (dB)	≥17	≥17
		0° direction beam front to back ratio (dB)	≥30	≥25

Mechanical Specifications	
Connector Type	4.3/10(F) x 16+MQ5 x 2+MQ4 x 2
Connector position	Bottom
Electrical Tilt Control	FDD: Integrated RET, Each Band Individually Control
	TDD: Integrated RET, Single internal RET control for all four antenna arrays
Mechanical Tilt Range	0-8
Radome Material	Fiberglass
Antenna Weight(kg)	35/40.5 (clamps incl.)
Bracket Diameter(mm)	50-125
Maximum Wind Speed(km/h)	200
Wind Load frontal [N] at 150 Km/h	1050
Wind Load rear side [N] at 150 Km/h	1170
Wind Load lateral [N] at 150 Km/h	510
Operating Temperature (°C)	-40 ~+60
Antenna Dimensions (H x W x D) (mm)	2280x497x197
Packing Size (H x W x D) (mm)	2520 x 572 x 272

Integrated RET Specifications	
Protocols	Compliant With AISGV2.0 And 3GPP
Supply Voltage, VDC	10–30DC
Power Consumption	<2W (standby); < 10W (motor activated)
Safety Standard	Compliant to EN 60950/UL 60950/ RoHs (Restriction of Hazardous Substances), CE
Lightning Protection Rating	IEC 61000-4-5 Current Pulse Profile, Line to Ground 8/20 us @ 6kA ≥±5 Repetitions Line to line , 8/20 us @ 3kA ≥±5 Repetitions
Connectors	2 x 8 Pins Connector According To IEC60130-9 AND AISG 1 x Daisy Chain In : Male 1 x Daisy Chain Out : Female Pin3:RS485B; Pin5:RS485A; Pin6:10~30V; Pin7: DC return Female connector: 4 PINs ,Male connector: 4 PINs

